

Legendary German Engineering

Quality, Design and Innovation



SWTNes 4265 & SKBes 4360





2.4" Touchscreen Display: Located behind the appliance door, this high-resolution and high-contrast 2.4" touchscreen display can be read from any angle. Stored menu options are Intuitive and easy-to-operate.




BioFresh-Plus: With the adjustable temperature range of 0°C and -2°C, BioFresh-Plus technology offers even more flexibility for your produce. The BioFresh-Plus drawer includes a versatile Fish & Seafood-Safe.




PowerCooling: A high-performance system that allows freshly stored items to be chilled rapidly while maintaining an even temperature throughout the interior. In this energy-efficient BluPerformance range, the fan switches off when the appliance door is opened, saving valuable energy.

Introducing Liebherr's award-winning Side-by-Side model from the BluPerformance range – the **SBSes 8486**. This eye-catching unit boasts an array of innovative solutions with six different climate zones, but its multi-temperature wine compartment is what makes it most unique! Enjoy added flexibility with BioFresh-Plus safe which offers an adjustable temperature range of 0°C and -2°C. Comes with a versatile Fish & Seafood-Safe.

SBSes 8486 PremiumPlus	Bio Fresh- Plus No Frost	lce Maker	Wine	Soft System	Soft Telescopic	Smart Steel	
*Side-by-Sides comprised of two models			SWTNes 4265				SKBes 4360
Energy consumption (kWh/yr) I Star rating			211 5.0				194 4.0
Compressors			1				1
Total capacity litres (L) - Gross I Net			327 279				413 366
Refrigerator gross (L) I Refrigerator net (L)			- -				250 234
Freezer gross (L) Freezer net (L)			154 126				- -
BioFresh gross (L) BioFresh net (L)			- -				163 132
Wine Zone gross (L) I Wine Zone net (L)			173 153 (48 bottles)				- -
Control system and display Child proof			2.4"Touch display Yes				2.4"Touch display Yes
PremiumPlus lighting Sabbath mode			Yes				Yes
SoftSystem hinge - assists closure			Yes				Yes
Door open Temperature : alarms					Vaal	Yes	Yes Yes I -
BioFreshPlus drawers on telescopic rails			Yes Yes				Yes -
BioFresh drawers on telescopic rails							2
SuperCool VarioSafe						- -	Yes Yes
SuperFrost VarioSpace			Yes Yes				- -
Integrated bottle shelf			-				- - Yes
Freezer drawers Lice cube drawer			4 1				- -
IceMaker Ice cube capacity (kg/24h)			Yes 1.2				- -
Stainless steel door with SmartSteel			Yes				Yes
Stainless steel walls with SmartSteel			Yes				Yes
Default hinge						Left	Right
Voltage (V) Rated Current (A)				22	0 - 240		220 - 240 1.2
Made in					Gern	nany	Germany



This increases the appliance depth by approximately 1.5 cm. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy consumption level. Water Connection



appliance which contains the locMaker. Water pressure must be between 0.15 MPa and 0.6 MPa (1.5 bar - 6 bar)

* These models are only bound for storing wine. Max. DIN norm bordeaus bottle capacity (0.75 l) as per norm NF H 35-124 (H:300.5 mm, Ø 76.1mm)