

BLU
Performance

Freshness With Style And Elegance

Quality, Design and Innovation

SGNPes 4365 & SKBes 4350

LIEBHERR



2.4" Touchscreen Display: Located behind the appliance door, this high-resolution and high-contrast 2.4" touchscreen display can be read from any angle. Stored menu options are intuitive and easy-to-operate.



BioFresh: When stored at Biofresh's precisely maintained temperature of 0°C and correct humidity level, nutrients in your food are retained. Our BioFresh drawers fully extend on telescopic rails and feature a self-closing mechanism.



PowerCooling: A high-performance system that allows freshly stored items to be chilled rapidly while maintaining an even temperature throughout the interior. In this energy-efficient BluPerformance range, the fan switches off when the appliance door is opened, saving valuable energy.

Volume, efficiency, economy, ease of use, and outstanding design are the key features of the **SBSes 8673** side-by-side fridge-freezer from Liebherr's BluPerformance series. High-quality components and materials, and perfect workmanship combined with precise touch electronics system are what made this appliance so efficient.


BioFresh technology allows your fruits, vegetables, meat, fish, and dairy products to stay fresher for longer. Meanwhile NoFrost technology ensures that this appliance never has to be defrosted. And thanks to its premium SmartSteel surface, this timeless elegant model is easy to clean and will definitely be a visual highlight in your home!

SBSes 8673
Premium




*Side-by-Sides comprised of two models	SGNPes 4365	SKBes 4350
Energy consumption (kWh/yr) Star rating	211 5.0	194 4.0
Compressors	1	1
Total capacity litres (L) - Gross Net	315 262	411 367
Refrigerator gross (L) Refrigerator net (L)	- -	250 234
Freezer gross (L) Freezer net (L)	315 262	- -
BioFresh gross (L) BioFresh net (L)	- -	161 133
Control system and display Child proof	2.4" Touch display Yes	2.4" Touch display Yes
PremiumPlus LED : lighting	- Yes	Yes -
Sabbath mode	Yes	Yes
SoftSystem hinge - assists closure	Yes	Yes
Door open Temperature : alarms	Yes Yes	Yes -
BioFresh drawers on telescopic rails	-	3
SuperCool VarioSafe	- -	Yes Yes
SuperFrost VarioSpace	Yes Yes	- -
Integrated bottle shelf	-	Yes
Freezer drawers Ice cube drawer	8 1	- -
IceMaker Ice cube capacity (kg/24h)	Yes 0.8	- -
Stainless steel door with SmartSteel	Yes	Yes
Stainless steel walls with SmartSteel	Yes	Yes
Default hinge	Left	Right
Voltage (V) Rated Current (A)	220 - 240 1.3	220 - 240 1.2
Made in	Germany	Germany

Installation Diagram



1 To achieve the indicated energy consumption level, the wall spacers provided with the appliance must be used. This increases the appliance depth by approximately 1.5 cm. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy consumption level.

Water Connection



a = 1100 mm
b = 700 mm
c = 110 mm
M = Solenoid valve

Plumbing must be installed adjacent to the side of the appliance which contains the IceMaker.
Water pressure must be between 0.15 MPa and 0.6 MPa (1.5 bar - 6 bar)